


# General Purpose Relays MKS


## Exceptionally Reliable General Purpose Relay now available with Lockable Test Button

- IEC Rating of 7A 250 V AC 50/60 Hz, General use 100,000 cycles.
- Mechanical indicator standard for all models.
- Optional features include lockable test button, LED indicator, diode surge suppression, varistor, reverse polarity, and alternate wiring styles.
- UL (RU/cRU), CE and TUV approved.
- RoHS Compliant.



## Features

### Two-way Action Test Button



## Model Number Structure

### Model Number Legend

MKS□□□□□□-□-□  
1 2 3 4 5 6 7

- Contact Form**  
2: DPDT  
3: 3PDT
- Terminals**  
P: Plug-in
- Mechanical Indicator/Test Button**  
Blank: Mechanical indicator  
I: Mechanical indicator and lockable test button
- LED Indicator**  
Blank: Standard  
N: LED indicator
- Coil Polarity**  
Blank: Standard  
1: Reverse polarity (DC coil only)
- Surge Absorption**  
Blank: Standard  
D: Surge absorber diode (DC coil only)  
V: Surge absorber varistor (AC coil only)
- Internal Connections DPDT**  
Blank: Standard  
2: Non Standard  
Internal Connections 3PDT  
5: Standard  
Blank: Non Standard  
2: Non Standard
- Rated Voltage**  
(Refer to "Coil Ratings".)

# Ordering Information

## ■ List of Models

| Type                                       | Terminals | Contact form | Internal connections<br>(See note 3.) | With mechanical indicator | With mechanical indicator<br>and lockable test button | Coil ratings |
|--|-----------|--------------|---------------------------------------|---------------------------|---|--------------|
| Basic Models                               | Plug-in   | DPDT         | Standard                              | MKS2P                     | MKS2PI  | AC/DC        |
|  |           |              | Non Standard                          | MKS2P-2                   | MKS2PI-2  |              |
|  |           | 3PDT         | Standard                              | MKS3P-5                   | MKS3PI-5  |              |
|  |           |              | Non Standard                          | MKS3P-2                   | MKS3PI-2  |              |
|  |           |              |                                       | MKS3P                     | MKS3PI  |              |
|  |           |              |                                       |                           |   |              |
| Models with LED Indicator<br>(See note 2.) |           | DPDT         | Standard                              | MKS2PN(1)                 | MKS2PIN(1)  | AC/DC        |
|  |           |              | Non Standard                          | MKS2PN(1)-2               | MKS2PIN(1)-2  |              |
|  |           | 3PDT         | Standard                              | MKS3PN(1)-5               | MKS3PIN(1)-5  |              |
|  |           |              | Non Standard                          | MKS3PN(1)-2               | MKS3PIN(1)-2  |              |
|  |           |              |                                       | MKS3PN(1)                 | MKS3PIN(1)  |              |
|  |           |              |                                       |                           |   |              |
| Models with Diode<br>(See note 2.)         |           | DPDT         | Standard                              | MKS2P(1)-D                | MKS2PI(1)-D   | DC           |
|  |           |              | Non Standard                          | MKS2P(1)-D-2              | MKS2PI(1)-D-2   |              |
|  |           | 3PDT         | Standard                              | MKS3P(1)-D-5              | MKS3PI(1)-D-5   |              |
|  |           |              | Non Standard                          | MKS3P(1)-D-2              | MKS3PI(1)-D-2   |              |
|  |           |              |                                       | MKS3P(1)-D                | MKS3PI(1)-D   |              |
|  |           |              |                                       |                           |   |              |
| Models with LED Indicator<br>and Diode     |           | DPDT         | Standard                              | MKS2PN-D                  | MKS2PIN-D   | DC           |
|  |           |              | Non Standard                          | MKS2PN-D-2                | MKS2PIN-D-2   |              |
|  |           | 3PDT         | Standard                              | MKS3PN-D-5                | MKS3PIN-D-5   |              |
|  |           |              | Non Standard                          | MKS3PN-D-2                | MKS3PIN-D-2   |              |
|  |           |              |                                       | MKS3PN-D                  | MKS3PIN-D   |              |
|  |           |              |                                       |                           |   |              |
| Models with Varistor                       |           | DPDT         | Standard                              | MKS2P-V                   | MKS2PI-V  | AC           |
|  |           |              | Non Standard                          | MKS2P-V-2                 | MKS2PI-V-2  |              |
|  |           | 3PDT         | Standard                              | MKS3P-V-5                 | MKS3PI-V-5  |              |
|  |           |              | Non Standard                          | MKS3P-V-2                 | MKS3PI-V-2  |              |
|  |           |              |                                       | MKS3P-V                   | MKS3PI-V  |              |
|  |           |              |                                       |                           |   |              |
| Models with LED Indicator<br>and Varistor  |           | DPDT         | Standard                              | MKS2PN-V                  | MKS2PIN-V   | AC           |
|  |           |              | Non Standard                          | MKS2PN-V-2                | MKS2PIN-V-2   |              |
|  |           | 3PDT         | Standard                              | MKS3PN-V-5                | MKS3PIN-V-5   |              |
|  |           |              | Non Standard                          | MKS3PN-V-2                | MKS3PIN-V-2   |              |
|  |           |              |                                       | MKS3PN-V                  | MKS3PIN-V   |              |
|  |           |              |                                       |                           |   |              |

**Note:** 1. When ordering, add the rated voltage to the model number. Rated voltages are given in the coil ratings table in the specifications.

Example: MKS2P DC48

Rated voltage

2. The DC coil comes in two types: standard coil polarity and reverse coil polarity. Refer to *Terminal Arrangement and Internal Connections*.

Example: MKS3PN1-5 DC24

Reverse coil polarity

3. Refer to *Terminal Arrangement and Internal Connections* for all wiring diagrams.

## ■ 10A Sockets (Order Separately)

| Item  | Type   | Model    |
|---|--------|----------|
| Track-mounted Socket                          | 8-pin  | PF083A-E |
|   | 11-pin | PF113A-E |
|   | 8-pin  | PF083A-D |
|   | 11-pin | PF113A-D |
| Hold-down Clip<br>(For PF083A-E and PF113A-E) |        | PFC-A1   |

# Specifications

## ■ Ratings

### Coil Ratings

| Rated voltage | Rated current |         | Coil resistance | Must operate voltage | Must release voltage      | Max. voltage   | Power consumption     |  |
|---------------|---------------|---------|-----------------|----------------------|---------------------------|--|-----------------------|--|
|               | 50 Hz         | 60 Hz   |                 |                      |                           |  |                       |  |
| AC            | 6 V           | 443 mA  | 385 mA          | 3.1 Ω                | 80% max. of rated voltage | 30% min. of rated voltage at 60 Hz<br>25% min. of rated voltage at 50 Hz | 110% of rated voltage | Approx. 2.3 VA at 60 Hz<br>Approx. 2.7 VA at 50 Hz |
|               | 12 V          | 221 mA  | 193 mA          | 13.7 Ω               |                           |  |                       |  |
|               | 24 V          | 110 mA  | 96.3 mA         | 48.4 Ω               |                           |  |                       |  |
|               | 110 V         | 24.2 mA | 21.0 mA         | 932 Ω                |                           |  |                       |  |
|               | 120 V         | 22.2 mA | 19.3 mA         | 1,130 Ω              |                           |  |                       |  |
|               | 220 V         | 12.1 mA | 10.5 mA         | 3,550 Ω              |                           |  |                       |  |
|               | 230 V         | 11.5 mA | 10.0 mA         | 4,250 Ω              |                           |  |                       |  |
|               | 240 V         | 11.0 mA | 9.6 mA          | 4,480 Ω              |                           |  |                       |  |
| DC            | 6 V           | 224 mA  |                 | 26.7 Ω               | 15% min. of rated voltage |  | Approx. 1.4 W         |  |
|               | 12 V          | 112 mA  |                 | 107 Ω                |                           |  |                       |  |
|               | 24 V          | 55.8 mA |                 | 430 Ω                |                           |  |                       |  |
|               | 48 V          | 28.1 mA |                 | 1,710 Ω              |                           |  |                       |  |
|               | 100 V         | 13.5 mA |                 | 7,390 Ω              |                           |  |                       |  |
|               | 110 V         | 12.3 mA |                 | 8,960 Ω              |                           |  |                       |  |

- Note:**
1. The rated current and coil resistance are measured at a coil temperature of 23°C with tolerances of +15%/–20% for AC rated current and ±15% for DC coil resistance.
  2. Performance characteristic data are measured at a coil temperature of 23°C.
  3. The maximum voltage is one that is applicable instantaneously to the Relay coil at 23°C and not continuously.
  4. For DC-operated Relays with the LED indicator built-in, add an LED current of approx. 5 mA to the rated current.

### Contact Ratings

| Load                    |    | Resistive load<br>(cosφ = 1) | Inductive load<br>(p.f. = 0.4) |
|-------------------------|----|------------------------------|--------------------------------|
| Contact mechanism       |    | Single                       |                                |
| Contact material        |    | AgSnIn                       |                                |
| Rated load              | NO | 10 A, 250 VAC<br>10A, 30 VDC | 7 A, 250 VAC                   |
|                         | NC | 5 A, 250 VAC<br>5 A, 30 VDC  |                                |
| Rated carry current     |    | 10 A                         |                                |
| Max. switching voltage  |    | 250 VAC, 250 VDC             |                                |
| Max. switching current  |    | 10 A                         |                                |
| Max. switching capacity | NO | 2,500 VA/300 W               |                                |
|                         | NC | 1,250 VA/150 W               |                                |

## ■ Characteristics

|                           |  |
|---------------------------|--|
| Contact resistance        | 100 mΩ max.  |
| Operate time              | AC: 20 ms max.<br>DC: 30 ms max.   |
| Release time              | 20 ms max.(40 ms max. for built-in diode models)   |
| Max. operating frequency  | Mechanical: 18,000 operations/hr (no load)<br>Electrical:1,800 operations/hr (at rated load)   |
| Insulation resistance     | 100 MΩ min. (at 500 VDC)   |
| Dielectric strength       | 2,500 VAC 50/60 Hz for 1 min. between coil and contacts<br>1,000 VAC 50/60 Hz for 1 min. between contacts of same polarity and terminals of the same polarity<br>2,500 VAC 50/60 Hz for 1 min. between current-carrying parts, non-current-carrying parts, and opposite polarity |
| Insulation method         | Basic insulation   |
| Impulse withstand voltage | 4.5 kV between coil and contacts (with 1.2 × 50 μs impulse wave)<br>3.0 kV between contacts of different polarity (with 1.2 × 50 μs impulse wave)  |
| Pollution degree          | 3  |
| Rated insulation voltage  | 250 V  |
| Vibration resistance      | Destruction:10 to 55 Hz, 1.5 mm double amplitude<br>Malfunction:10 to 55 Hz, 1.0 mm double amplitude   |
| Shock resistance          | Destruction:1,000 m/s <sup>2</sup> (approx. 100 G)<br>Malfunction:100 m/s <sup>2</sup> (approx. 10 G)  |
| Life expectancy           | Mechanical: 5,000,000 operations min.<br>Electrical:100,000 operations min.  |
| Min. permissible load     | 10 mA at 1 VDC P level: λ <sub>60</sub> =0.1 × 10 <sup>-6</sup> / ops  |
| Ambient temperature       | Operating: -40 to 60°C (with no icing or condensation)   |
| Ambient humidity          | Operating: 5% to 85%   |
| Weight                    | Approx. 90 g   |

Note: 1. The values given above are initial values.  
2. Ambient temperature of models with LED indicator is -25 to 60°C.

## ■ Approved Standards

UL Recognized (File No. E41515) -- Ambient Temp. = 40°C

| Coil ratings                 | Contact ratings |  | Operations |
|------------------------------|-----------------|--|------------|
| 6 to 110 VDC<br>6 to 240 VAC | N.O. contact    | 10 A, 250 V AC 50/60 Hz (Resistive)<br>10 A, 30 V DC (Resistive)<br>7 A, 250 V AC 50/60 Hz (General Use) | 100,000    |
|                              | N.C. contact    | 10 A, 250 V AC 50/60 Hz (Resistive)<br>10 A, 30 V DC (Resistive)<br>7 A, 250 V AC 50/60 Hz (General Use) | 100,000    |

Note: 10A UL ratings are with no load on the other contact set.

CSA Certified by  <sup>US</sup>

IEC Standard/TUV Certification: IEC61810-1  
(Certification No. R50104853)


| Coil ratings   | Contact ratings |  | Operations |
|--|-----------------|--|------------|
| 6, 12, 24, 48,<br>100, 110 VDC<br>6, 12, 24, 100,<br>110, 200, 220,<br>240 VAC | N.O. contact    | 10 A, 250 V AC 50/60 Hz (Resistive)<br>10 A, 30 V DC (Resistive)<br>7 A, 250 V AC 50/60 Hz (General Use) | 100,000    |
|  | N.C. contact    | 5 A, 250 V AC 50/60 Hz (Resistive)<br>5 A, 30 V DC (Resistive)<br>7 A, 250 V AC 50/60 Hz (General Use)   | 100,000    |

Note: Maximum carrying current per TUV Certification is 9 A when new MK-S relays are mounted in PF083A-E or PF113A-E Sockets.


## Engineering Data

### ■ Reference Data

#### Maximum Switching Power



#### Rated Carry Current vs. Ambient Rated Temperature




Note: The lower limit of the ambient operating temperature for models with built-in operation indicators is -25°C.


# Dimensions

Note: All units are in millimeters unless otherwise indicated.

## Models without Test Button









## Models with Lockable Test Button




## Track Mounted Sockets

See below for Socket dimensions.


| Poles                 | Finger-protection models  |   | —   |
|-----------------------|---|---|---|
| Maximum carry current | 10 A  |   | 5 A   |
| 2 poles               | PF083A-E<br>  | PF083A-D<br>  | PF083A<br>  |
| 3 poles               | PF113A-E<br> | PF113A-D<br> | PF113A<br> |

Note: If using the PF083A or PF113A Sockets, be sure the maximum carrying current is 5 A or less. When using finger-protection sockets, make sure the connecting wire terminals are Y-shaped.


### PF083A-E (Conforming to EN 5022)




### Terminal Arrangement




### Mounting Holes




### PF113A-E (Conforming to EN 5022)




### Terminal Arrangement




### Mounting Holes




PF083A-D




Terminal Arrangement




Mounting Holes




PF113A-D



Terminal Arrangement




Mounting Holes



Hold-down Clips



PFC-A1

(2 pieces per set)





Mounting Tracks

PFP-100N, PFP-50N  
(Conforming to EN 50022)




PFP-100N2  
(Conforming to EN 50022)



\* The figure in parenthesis is for PFP-50N.


Mounting Height with Sockets




Note: PF083A(-E) and PF113A(-E) allow either track or screw mounting.

# Terminal Arrangement/Internal Connection (Bottom View)


**Basic Models  
(AC/DC Coil)**




**LED Indicator Type  
(AC Coil)**




**LED Indicator Type  
(DC Coil:  
Standard Polarity)**




**LED Indicator Type  
(DC Coil:  
Reverse Polarity)**




**Diode Type  
(DC Coil:  
Standard Polarity)**




**Diode Type  
(DC Coil:  
Reverse Polarity)**




**LED Indicator and Diode Type (DC Coil)**



**Varistor Type (AC Coil)**



**LED Indicator and Varistor Type (AC Coil)**



## Safety Precautions

### ■ Safety Precautions for Correct Use

#### Installation

Recommend mounting MK-S Relay so that side with wiring diagram is facing down.

#### Handling

Check coil polarity when wiring LED Indicator and Diode Models.

#### Test Button

Do not use the test button for any purpose other than testing. Be sure not to touch the test button accidentally as this will turn the contacts ON. Before using the test button, confirm that circuits, the load, and any other connected item will operate safely.

Check that the test button is released before turning ON relay circuits.

If the test button is pulled out too forcefully, it may bypass the momentary testing position and go straight into the locked position.

Use an insulated tool when you operate the test button.

Models with test buttons or LED indicators fulfill the requirements for reinforced insulation between live parts and the front of cover only when the Relay is in a complete condition, i.e. with the nameplate, nameplate frame, test button, and slider in place. If any of these parts are removed, only the requirements for basic insulation are fulfilled.



# Terms and Conditions of Sale

1. **Offer; Acceptance.** These terms and conditions (these "Terms") are deemed part of all quotes, agreements, purchase orders, acknowledgments, price lists, catalogs, manuals, brochures and other documents, whether electronic or in writing, relating to the sale of products or services (collectively, the "Products") by Omron Electronics LLC and its subsidiary companies ("Omron"). Omron objects to any terms or conditions proposed in Buyer's purchase order or other documents which are inconsistent with, or in addition to, these Terms.
2. **Prices; Payment Terms.** All prices stated are current, subject to change without notice by Omron. Omron reserves the right to increase or decrease prices on any unshipped portions of outstanding orders. Payments for Products are due net 30 days unless otherwise stated in the invoice.
3. **Discounts.** Cash discounts, if any, will apply only on the net amount of invoices sent to Buyer after deducting transportation charges, taxes and duties, and will be allowed only if (i) the invoice is paid according to Omron's payment terms and (ii) Buyer has no past due amounts.
4. **Interest.** Omron, at its option, may charge Buyer 1-1/2% interest per month or the maximum legal rate, whichever is less, on any balance not paid within the stated terms.
5. **Orders.** Omron will accept no order less than \$200 net billing.
6. **Governmental Approvals.** Buyer shall be responsible for, and shall bear all costs involved in, obtaining any government approvals required for the importation or sale of the Products.
7. **Taxes.** All taxes, duties and other governmental charges (other than general real property and income taxes), including any interest or penalties thereon, imposed directly or indirectly on Omron or required to be collected directly or indirectly by Omron for the manufacture, production, sale, delivery, importation, consumption or use of the Products sold hereunder (including customs duties and sales, excise, use, turnover and license taxes) shall be charged to and remitted by Buyer to Omron.
8. **Financial.** If the financial position of Buyer at any time becomes unsatisfactory to Omron, Omron reserves the right to stop shipments or require satisfactory security or payment in advance. If Buyer fails to make payment or otherwise comply with these Terms or any related agreement, Omron may (without liability and in addition to other remedies) cancel any unshipped portion of Products sold hereunder and stop any Products in transit until Buyer pays all amounts, including amounts payable hereunder, whether or not then due, which are owing to it by Buyer. Buyer shall in any event remain liable for all unpaid accounts.
9. **Cancellation; Etc.** Orders are not subject to rescheduling or cancellation unless Buyer indemnifies Omron against all related costs or expenses.
10. **Force Majeure.** Omron shall not be liable for any delay or failure in delivery resulting from causes beyond its control, including earthquakes, fires, floods, strikes or other labor disputes, shortage of labor or materials, accidents to machinery, acts of sabotage, riots, delay in or lack of transportation or the requirements of any government authority.
11. **Shipping; Delivery.** Unless otherwise expressly agreed in writing by Omron:
  - a. Shipments shall be by a carrier selected by Omron; Omron will not drop ship except in "break down" situations.
  - b. Such carrier shall act as the agent of Buyer and delivery to such carrier shall constitute delivery to Buyer;
  - c. All sales and shipments of Products shall be FOB shipping point (unless otherwise stated in writing by Omron), at which point title and risk of loss shall pass from Omron to Buyer; provided that Omron shall retain a security interest in the Products until the full purchase price is paid;
  - d. Delivery and shipping dates are estimates only; and
  - e. Omron will package Products as it deems proper for protection against normal handling and extra charges apply to special conditions.
12. **Claims.** Any claim by Buyer against Omron for shortage or damage to the Products occurring before delivery to the carrier must be presented in writing to Omron within 30 days of receipt of shipment and include the original transportation bill signed by the carrier noting that the carrier received the Products from Omron in the condition claimed.
13. **Warranties.** (a) **Exclusive Warranty.** Omron's exclusive warranty is that the Products will be free from defects in materials and workmanship for a period of twelve months from the date of sale by Omron (or such other period expressed in writing by Omron). Omron disclaims all other warranties, express or implied. (b) **Limitations.** OMRON MAKES NO WARRANTY OR REPRESENTATION, EXPRESS OR IMPLIED, ABOUT NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OF THE PRODUCTS. BUYER ACKNOWLEDGES THAT IT ALONE HAS DETERMINED THAT THE PRODUCTS WILL SUITABLY MEET THE REQUIREMENTS OF THEIR INTENDED USE. Omron further disclaims all warranties and responsibility of any type for claims or expenses based on infringement by the Products or otherwise of any intellectual property right. (c) **Buyer Remedy.** Omron's sole obligation hereunder shall be, at Omron's election, to (i) replace (in the form originally shipped with Buyer responsible for labor charges for removal or replacement thereof) the non-complying Product, (ii) repair the non-complying Product, or (iii) repay or credit Buyer an amount equal to the purchase price of the non-complying Product; provided that in no event shall Omron be responsible for warranty, repair, indemnity or any other claims or expenses regarding the Products unless Omron's analysis confirms that the Products were properly handled, stored, installed and maintained and not subject to contamination, abuse, misuse or inappropriate modification. Return of any Products by Buyer must be approved in writing by Omron before shipment. Omron Companies shall not be liable for the suitability or unsuitability or the results from the use of Products in combination with any electrical or electronic components, circuits, system assemblies or any other materials or substances or environments. Any advice, recommendations or information given orally or in writing, are not to be construed as an amendment or addition to the above warranty. See <http://www.omron247.com> or contact your Omron representative for published information.
14. **Limitation on Liability; Etc.** OMRON COMPANIES SHALL NOT BE LIABLE FOR SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, LOSS OF PROFITS OR PRODUCTION OR COMMERCIAL LOSS IN ANY WAY CONNECTED WITH THE PRODUCTS, WHETHER SUCH CLAIM IS BASED IN CONTRACT, WARRANTY, NEGLIGENCE OR STRICT LIABILITY. Further, in no event shall liability of Omron Companies exceed the individual price of the Product on which liability is asserted.
15. **Indemnities.** Buyer shall indemnify and hold harmless Omron Companies and their employees from and against all liabilities, losses, claims, costs and expenses (including attorney's fees and expenses) related to any claim, investigation, litigation or proceeding (whether or not Omron is a party) which arises or is alleged to arise from Buyer's acts or omissions under these Terms or in any way with respect to the Products. Without limiting the foregoing, Buyer (at its own expense) shall indemnify and hold harmless Omron and defend or settle any action brought against such Companies to the extent based on a claim that any Product made to Buyer specifications infringed intellectual property rights of another party.
16. **Property; Confidentiality.** Any intellectual property in the Products is the exclusive property of Omron Companies and Buyer shall not attempt to duplicate it in any way without the written permission of Omron. Notwithstanding any charges to Buyer for engineering or tooling, all engineering and tooling shall remain the exclusive property of Omron. All information and materials supplied by Omron to Buyer relating to the Products are confidential and proprietary, and Buyer shall limit distribution thereof to its trusted employees and strictly prevent disclosure to any third party.
17. **Export Controls.** Buyer shall comply with all applicable laws, regulations and licenses regarding (i) export of products or information; (ii) sale of products to "forbidden" or other proscribed persons; and (iii) disclosure to non-citizens of regulated technology or information.
18. **Miscellaneous.** (a) **Waiver.** No failure or delay by Omron in exercising any right and no course of dealing between Buyer and Omron shall operate as a waiver of rights by Omron. (b) **Assignment.** Buyer may not assign its rights hereunder without Omron's written consent. (c) **Law.** These Terms are governed by the law of the jurisdiction of the home office of the Omron company from which Buyer is purchasing the Products (without regard to conflict of law principles). (d) **Amendment.** These Terms constitute the entire agreement between Buyer and Omron relating to the Products, and no provision may be changed or waived unless in writing signed by the parties. (e) **Severability.** If any provision hereof is rendered ineffective or invalid, such provision shall not invalidate any other provision. (f) **Setoff.** Buyer shall have no right to set off any amounts against the amount owing in respect of this invoice. (g) **Definitions.** As used herein, "including" means "including without limitation"; and "Omron Companies" (or similar words) mean Omron Corporation and any direct or indirect subsidiary or affiliate thereof.

## Certain Precautions on Specifications and Use

1. **Suitability of Use.** Omron Companies shall not be responsible for conformity with any standards, codes or regulations which apply to the combination of the Product in the Buyer's application or use of the Product. At Buyer's request, Omron will provide applicable third party certification documents identifying ratings and limitations of use which apply to the Product. This information by itself is not sufficient for a complete determination of the suitability of the Product in combination with the end product, machine, system, or other application or use. Buyer shall be solely responsible for determining appropriateness of the particular Product with respect to Buyer's application, product or system. Buyer shall take application responsibility in all cases but the following is a non-exhaustive list of applications for which particular attention must be given:
  - (i) Outdoor use, uses involving potential chemical contamination or electrical interference, or conditions or uses not described in this document.
  - (ii) Use in consumer products or any use in significant quantities.
  - (iii) Energy control systems, combustion systems, railroad systems, aviation systems, medical equipment, amusement machines, vehicles, safety equipment, and installations subject to separate industry or government regulations.
  - (iv) Systems, machines and equipment that could present a risk to life or property. Please know and observe all prohibitions of use applicable to this Product.

NEVER USE THE PRODUCT FOR AN APPLICATION INVOLVING SERIOUS RISK TO LIFE OR PROPERTY OR IN LARGE QUANTITIES WITHOUT ENSURING THAT THE SYSTEM AS A WHOLE HAS BEEN DESIGNED TO ADDRESS THE RISKS, AND THAT THE OMRON'S PRODUCT IS PROPERLY RATED AND INSTALLED FOR THE INTENDED USE WITHIN THE OVERALL EQUIPMENT OR SYSTEM.
2. **Programmable Products.** Omron Companies shall not be responsible for the user's programming of a programmable Product, or any consequence thereof.
3. **Performance Data.** Data presented in Omron Company websites, catalogs and other materials is provided as a guide for the user in determining suitability and does not constitute a warranty. It may represent the result of Omron's test conditions, and the user must correlate it to actual application requirements. Actual performance is subject to the Omron's Warranty and Limitations of Liability.
4. **Change in Specifications.** Product specifications and accessories may be changed at any time based on improvements and other reasons. It is our practice to change part numbers when published ratings or features are changed, or when significant construction changes are made. However, some specifications of the Product may be changed without any notice. When in doubt, special part numbers may be assigned to fix or establish key specifications for your application. Please consult with your Omron's representative at any time to confirm actual specifications of purchased Product.
5. **Errors and Omissions.** Information presented by Omron Companies has been checked and is believed to be accurate; however, no responsibility is assumed for clerical, typographical or proofreading errors or omissions.

---

**Note:** This datasheet is provided as a guideline for selecting products. Do not use this document to operate the Unit.

**ALL DIMENSIONS SHOWN ARE IN MILLIMETERS.**

To convert millimeters into inches, multiply by 0.03937. To convert grams into ounces, multiply by 0.03527.

# OMRON

**OMRON ELECTRONICS LLC • THE AMERICAS HEADQUARTERS**

Schaumburg, IL USA • 847.843.7900 • 800.556.6766 • [www.omron247.com](http://www.omron247.com)

**OMRON CANADA, INC. • HEAD OFFICE**

Toronto, ON, Canada • 416.286.6465 • 866.986.6766 • [www.omron247.com](http://www.omron247.com)

**OMRON ELETRÔNICA DO BRASIL LTDA • HEAD OFFICE**

São Paulo, SP, Brasil • 55.11.2101.6300 • [www.omron.com.br](http://www.omron.com.br)

**OMRON ELECTRONICS MEXICO SA DE CV • HEAD OFFICE**

Apodaca, N.L. • 52.811.156.99.10 • 001.800.556.6766 • [mela@omron.com](mailto:mela@omron.com)

**OMRON ARGENTINA • SALES OFFICE**

Cono Sur • 54.11.4783.5300

**OMRON CHILE • SALES OFFICE**

Santiago • 56.9.9917.3920

**OTHER OMRON LATIN AMERICA SALES**

54.11.4783.5300

© 2009 Omron Electronics LLC

Cat. No. X301-E-1 6/09

Specifications are subject to change without notice.

Printed in U.S.A.